

## CLIPFIT FUSE-HOLDERS FOR COMPACT DIMENSION FUSE-LINKS

TYPE LCF

230/240 & 400/415 Volt Compact Dimension Fuse-Holders to IEC 60269-2/BS 88-2

Rated Voltages 240 & 415V a.c. Breaking Capacities 20kA at 240V, 80kA at 415V



### Alternative Colours:

For White, substitute WH for BK


For Green, substitute GN for BK (20A only)

Lawson Clipfit Fuse-Holders are available with four wiring configurations:

Double front connected (FC/FC)

Front/bushbar connected (FC/BBC)

Front/back connected (FC/BC) Double back connected (BC/BC)



## PRODUCT DETAILS

### SPECIFICATIONS

List Reference	Current Rating (A)	Laswson Fuse Type	Voltage Rating (V)	Breaking Capacity (kA)	Solid Link	Colour
LCF 20 FC/FC BK	20	SS (E1)	240V a.c. 415V a.c.	20kA a.c. 80kA a.c.	SLE1	Black
			240V a.c. 415V a.c.	20kA a.c. 80kA a.c.		
			240V a.c. 415V a.c.	20kA a.c. 80kA a.c.		
LCF 32 FC/FC BK	32	NS (F1)	240V a.c. 415V a.c.	20kA a.c. 80kA a.c.	SLF1	Black
			240V a.c. 415V a.c.	20kA a.c. 80kA a.c.		
			240V a.c. 415V a.c.	20kA a.c. 80kA a.c.		
LCF 63 FC/FC BK	63	MES (F2)	240V a.c. 415V a.c.	20kA a.c. 80kA a.c.	SLF2	Black
			240V a.c. 415V a.c.	20kA a.c. 80kA a.c.		
			240V a.c. 415V a.c.	20kA a.c. 80kA a.c.		
Space Carriers		Space Cable Shrouds (Grey)		DIN-Rail Adaptor		
LCF 20 CA BK		LCF 20 SH		All bases include integral DIN-Rail Adaptor		
LCF 32 CA BK		LCF 32 SH				
LCF 63 BA CK		LCF 63 SH				

