

REYROLLE PATTERN INDUSTRIAL FUSE-LINKS

TYPE LGP

400/415 Volt Industrial Fuse-Links to IEC 60269-2/BS 88-2

Rated Voltages 415V a.c. 250V d.c Breaking Capacities 80kA a.c. 40kA d.c. Ranges and Utilisation Category gG/gM



Lawson Type "LGP" fuse-links are for use in REYROLLE pattern Type 2 and Type 20 fuse-holders.

The LGP-2 fuse-link range has bolted tag connections except for the LGPF-2F which is fitted with wire tails.

The LGP-20 fuse-link range has plain tag connections except for Type LGPE-20E now replaced by the Lawson 'ME' range.



PRODUCT DETAILS

REYROLLE PATTERN FUSE-LINKS

List Reference	Current Rating (A)	Voltage Rating (V)	Breaking Capacity (kA)	BS Standard	IEC Standard
LGPF-2F	26,10,16,20,32,40,50,63,80,100	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPG-2G	160,200	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPH-2H	160,200,250,315	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPJ-2H	355,400	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPJ-2J	500,630	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPF-20F	16,32,40,50,63,80,100	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPG-20G	125,160,200	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPH-20H	315,355,400	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPJ-20J	250,315,355,400,500, 630	415V a.c.	80kA a.c.	BS 88-1	60269-1
LGPE-20E	5-100	415V a.c.	80kA a.c.	BS 1361-11a	60269-1