

NEOZED FUSE-LINKS

TYPE LNZ

400 Volt Neozed Fuse-Links to IEC 60269-3

Rated Voltage 400V a.c. Breaking Capacity 50kA Breaking Range and Utilisation Category gG



400 Volt Neozed Fuse-links are special fuses that protect the breakers in low-voltage power circuits with high short-circuit levels. They are accompanied by the 400 Volt Neozed Fuse-holders.

Also available: Ranges of Fuse-Links for motor circuit and semiconductor protection



PRODUCT DETAILS

CURRENT RATINGS AND PRINCIPAL DIMENSIONS

List Reference		Current Rating (A)	Principal Dimensions	
400V a.c.	440V a.c.		Length mm	Diameter mm
LNZ11-400	LNZ11-440	2,4,6,10,16,20,25,35,50,63	36	11
LNZ15-400	LNZ15-440	2,4,6,10,16,20,25,35,50,63	36	15
LNZ22-400	-	80	43	22

FUSE-BASES AND ACCESSORIES

400 Volt Neozed Fuse-Holders to IEC 60269-3

Rated Voltage 400V a.c. Breaking Capacity 50kA

In addition to all sizes of Fuse-Bases, the range of accessories includes replacement screw caps and gauge pieces.

