LAWSON FUSES LIMITED

# PRODUCT INFORMATION

## MINIATURE FUSE-LINKS — TYPE MIN

### 230/240 Volt Miniature Fuse-Links to IEC 60127

Rated Voltage 250V a.c. Breaking Capacities – Various

Lawson type MIN Fuse-Links are available to meet a wide variety of applications.

Miniature and other small dimensioned Fuse-Links are grouped into several different application categories and comply with different specifications.

Many different types are available with current ratings from 10mA to 30A

## PRODUCT DETAILS

### CURRENT RATINGS AND PRINICIPAL DIMENSIONS - 5 X 20

| Type Reference | Dimensions (mm) | Operating Characteristics | Body Material | Rating | | Fuse Holder Type |
|---|---|---|---|---|---|---|
| | | | | mA | Amps | |
| PDC | 5 X 20 | Fast | Glass | 32,40,50,63,80,100,125,160<br>200, 315, 400, 500, 630, 800 | 1, 1.25,1.6,2,2.5,3.15,4,5<br>6.3,8,10,15 | KP |
| PCC | | | Ceramic | 32,40,50,63,80 100,125,160<br>200,315,400,500,630,000 | 1, 1.25,1.6,2,2.5,3.15,4,5<br>6.3,8,10 | |
| PDC-S | | Slow | Glass | 32,40,50,63,80 100,125,160<br>200, 315, 400, 500, 630, 800 | 1, 1.25,1.6,2,2.5,3.15,4,5<br>6.3,8,10 | |
| PCC-S | | | Ceramic | 125,160,200,250,315<br>400,500,630,800 | 1, 1.25,1.6,2,2.5,3.15,4,5<br>6.3,8,10 | |
| PCC-UR | | Ultra Fast | | | 1.6,2,3.15,4,5,8,10 | |

### CURRENT RATINGS AND PRINCIPAL DIMENSIONS - 6.3 X 32

| Type Reference | Dimensions (mm) | Operating Characteristics | Body Material | Rating | | Fuse Holder Type |
|---|---|---|---|---|---|---|
| | | | | mA | Amps | |
| KDC | 6.3 X 3.2 | Fast | Glass | 10,32,40,63,100,125,150,175,187<br>200,250,300,375,500,600, 750 | 1, 1.25,1.5,1.6,2,2.5,3,4,5,<br>6,7,8,10 | K |
| KCC | | | Ceramic | 125,250,375,500,750 | 1,2,3,4,5,6,7,8,10,12,15<br>20,25,30 | |
| KCD-S | | Slow | Glass | 10,32,40,63,100,125,150,175,187, 200<br>250,300,375,400,500,600,700,750, 800 | 5,6,7,8,20,25,30 | |
| KCC-S | | | Ceramic | 10,32,63,100,125,150,175,187, 200<br>250,300,375,400,500,600,700,750, 800 | 1, 1.25,1.5,1.6,2,2.5,3,4,5,<br>6,7,8,10,12,15,20,25,30 | |
| KCC-UR | | Ultra Fast | | | 1,1.25,2,3,4,5,6,7,8,10,12<br>15,20,25,30 | |

### CURRENT RATINGS AND PRINCIPAL DIMENSIONS - 5 x 25

| Type Reference | Dimensions (mm) | Operating Characteristics | Body Material | Rating | |
|---|---|---|---|---|---|
| | | | | mA | Amps |
| TDC | 5 x 25 | Fast | Glass | 80,100,125,160,200<br>250,315,400,500,630, 800 | 1, 1.25,1.6,2,2.5,3.15,4,5<br>6.3,8,10 |
| TCC | | | Ceramic C/W Indicator | | 1.6,2,2.5,3.15,4,5,6.3,8,10 |
| TDC-M | | | Glass | 80,100,125,160,200<br>250,315,400,500,630, 800 | 1, 1.25,1.6,2,2.5,3.15,4,5<br>6.3,8,10 |
| TCC-M | | | Ceramic<br>C/W Indicator | 80,100,125,160,200<br>250,315,400,500,630, 800 | 1, 1.25,1.6,2,2.5,3.15,4,5<br>6.3,8,10 |

Intertek

MADE IN BRITAIN