

BS INDUSTRIAL FUSE-LINKS WITH BOLTED CONNECTIONS

TYPE SS

690 Volt Industrial Fuse-Links to IEC 60269-2/BS 88-2

Rated Voltages 690V a.c. 250V d.c. Breaking Capacities 80kA a.c. 40kA d.c. Breaking Ranges and Utilisation Category gG/gM



Lawson Type "SS" fuse-links are for use in industrial applications and have been approved by leading authorities including Electricity Supply Authorities.

Dimensions and current ratings of the Lawson type SS Industrial Fuse-Links comply with the standardized requirements of IEC 60269-2 and BS 88-2. Additional types and current ratings are included in the range.

Lawson type SS Industrial Fuse-Links can be fitted in Boltin Fuse-Holders or suitable fusegear.



PRODUCT DETAILS

OFFSET TAG FUSE-LINKS

List Reference	Current Rating (A)	BS88 Reference	Fixing Centres G1		Fixing Centres G2	
			mm	ins	mm	ins
SSA1	2,4,6,10,16,20	A1	44.5	1 3/4		
SSA2	2,4,6,10,16,20,25,32	A2	73	2 7/8		
SSA3	35,40,50,63	A3	73	2 7/8		
SSA4	32,40,50,63,80,100	A4	94	3 11/16		
SSFP	125,160,200	(as A4)	94	3 11/16		
85SSM	355,400	-	104	4	22	7/8
86SST	450,500,560,630,670,710,750, 800	-	102	4	22	7/8

CENTRAL TAG FUSE-LINKS

List Reference	Current Rating (A)	BS88 Reference	Fixing Centres G1		Fixing Centres G2	
			mm	ins	mm	ins
SSB	2,4,6,10,16,20,25,32,35,40,50,63	-	97	3 13/16	-	-
SSBC	2,4,6,10,16,20,25,32,35,40,50,63	(as B1)	111	4 3/8	-	-
SSB1	80,100	B1	111	4 3/8	-	-
SSB2	125,160,200	B2	111	4 3/8	-	-
84SSF	125,160,200	-	99	4 29/32	-	-
SSB3	250,315	B3	111	4 3/8	-	-
84SSK	250,315	-	133	3 29/32	-	-
SSKM	125,160,200,250,315	-	133	5 1/4	-	-
SSB4	355,400	B4	111	4 3/8	-	-
SSC1	355,400	C1	133	5 1/4	184	7 1/4
SSMT	355,400	-	165	6 1/2	229	9
SSC2	450,500,560,630	C2	133	5 1/4	184	7 1/4
SST	450,500,560,630	-	165	6 1/2	229	9
SSC3	670,710,750,800	C3	133	5 1/4	184	7 1/4
SSLT	670,710,750,800	-	165	6 1/2	229	9
SSLU	450,500,560,630,670,710,750, 800	D1	149	5 7/8	32	1 1/4